


814X-02 Sprayball 180° downward – 316L



Dimensions				Applied Pressure	Flowrates		Cleaning Diameter	Stock No
Coverage	Supply tube OD	Ball diameter	Spray hole diameter	Bar	Imp Gal/hr	m3/hr	Max. tank dia recommended (m)	
180D	3/4"	50mm	1.6mm	1	703	3.2	3.4	8141-6019
180D	1"	65mm	2.5mm	1.5	2813	12.8	5.0	8144-6026
180D	1.5"	65mm	2.5mm	2.0	3384	15.4	8.1	8144-6038

Other options available

TECHNICAL DATA	
Material	316 Stainless Steel
Material Certification	BS EN 10204/FIN 50049 3.1 for all wetted parts
Finish	Internal 0.8Ra as standard (0.4Ra option available)
Pressure/Temperature	1-2 Bar Typ. / 0-134 °C
Tolerance	+/- 1mm
Notes	Dimensions are provided in good faith. Seals must be chosen for required operating medium and temperature
GENERAL CAPABILITIES	
Design and System Fabrication, Hygienic Process Plant, Project Management, In-house Manual and Orbital Welding, Machining, Fabrication and Polishing, Component Customisation	
Full materials certification, weld maps, logs, welder qualifications and weld procedures, pickling, passivation and ferroxyl certification.	

D814X-02-V04 ECN 1034

CUSTOMISED STAINLESS STEEL SYSTEMS, FABRICATIONS AND COMPONENTS

Axium Process Ltd

Hendy Industrial Estate, Hendy, Swansea, UK SA4 0XP

Tel: +44 (0) 1792 883882

Fax: +44 (0) 1792 886049

Email: info@axiumprocess.com

Web: www.axiumprocess.com



FS 83081

All data is provided in good faith and is subject to change