DATA SHEET


www.axiumprocess.com



5061

Clamp Y piece 316L

Nom size inch	L1	L2	Stock No
*1/2"	31.1	75.1	5061-6013
*3/4"	38.8	93.8	5061-6019
*1"	47.0	113.5	5061-6026
*1 ½"	63.0	152.0	5061-6038
*2"	78.8	190.3	5061-6051
*2 ½"	94.8	228.8	5061-6064
*3"	110.7	267.3	5061-6076
*4"	142.5	344.0	5061-6102



TECHNICAL DATA		
Associated Standards	*BS 4825-3 (1"-4" inclusive)	
Material	316L Stainless Steel	
Material Certification	BS EN 10204/DIN 50049 3.1 for all wetted parts	
Finish	Welds removed ID & OD, polished 0.8Ra (0.4Ra available)	
Clamp Fittings Range	Unions, ferrules, blanks, tees, bends, hoseliners, adaptors, concentric & eccentric reducers, Y pieces	
Seals	FDA & USP Class VI approved polymers including EPDM, Nitrile, Silicone, Platinum Cured Silicone, Encapsulated & Solid PTFE, Viton® (Viton is a registered trade mark of Dupont Dow Elastomers).	
Notes	Dimensions are provided in good faith. Seals must be chosen for required operating medium and temperature	
	GENERAL CAPABILITIES	
Design and System Fab	rication, Hygienic Process Plant, Project Management, In-house Manual and Orbital Welding,	

Machining, Fabrication and Polishing, Component Customisation

Full materials certification, weld maps, logs, welder qualifications and weld procedures, pickling, passivation and ferroxyl certification.

D5061-V04 ECN 725

CUSTOMISED STAINLESS STEEL SYSTEMS, FABRICATIONS AND COMPONENTS

Axium Process Ltd

Hendy Industrial Estate, Hendy, Swansea, UK SA4 0XP

Tel: +44 (0) 1792 883882 Fax: +44 (0) 1792 886049 Email: info@axiumprocess.com Web: www.axiumprocess.com



All data is provided in good faith and is subject to change